

| Product description | Methods | Product data |
|-----------------------|------------------|-----------------------------|
| Construction | | |
| Structure | ISO 2424 | Woven loop pile |
| Pile material | DIR 96/73, 96/74 | 100% Polyamide |
| Coloration | - | Continue |
| Backing | eTL | Ecotrust 350, 100% Recycled |
| Dimensions | ISO 3018 | 48x48/96x96 cm |
| Dimensional stability | EN 986 | <0,2% |
| Total thickness | ISO 1765 | Ca. 5,0 mm. |
| Total carpet weight | ISO 8543 | Ca. 2.500 g/m ² |
| Pile yarn weight | eTL | 625 g/m ² |
| edge soil protection | eTL | Yes |

Performance ratings

| | | |
|--------------------------------|------------------------|------------------------|
| Performance areas | EN15114 | 33 Commercial - Heavy |
| | eTL | Contract certifikat |
| Performance areas | Gulvbranchen | Klasse 33 |
| Suitable for castor chairs | EN 985 | Yes, constant use |
| Suitable for stairs | EN 1963 | Yes |
| Static control | eTL | Permanently antistatic |
| Body walking test | ISO 6356 | Antistatic |
| Acou.insu. from impact noise | EN ISO 717-2 | 16 dB |
| Acoustical absorption | ISO 354 | 0,20 aW |
| | Sound absorption class | E |
| Suitable for heated floors | ISO 8302 | Yes |
| Colour fastness to light | ISO 105-B02 | >5 |
| Colour fastness to rubbing wet | EN ISO 105-X12 | >3 |
| Colour fastness to rubbing dry | EN ISO 105-X12 | >3-4 |
| Colour fastness to water plain | EN ISO 105-E01 | >3-4 |

Safety & Environment

| | | |
|------------------|----------------------------------|----------------------|
| CE Labeling | Slip resistance EN 13893 | Class DS |
| | EN 14041 | Certified |
| EC Certificate | EN 14041 | 0845-CPD-CX10026CMod |
| Reaction to fire | DK,MK GODKENDELSE | Godkendt |
| | D,DIBT AbZ.no. | Z-156.601-377 |
| | CH,VKF/AEAI | Cfl-s1 |
| | EN13501-1 euro class | Cfl-s1 |
| CE Labeling | Declaration of Performance | 9711-26CMOD |
| Indoor air | DIM Certifikat | No.006 |
| | LEED | Green label plus |
| | BASTA | Registered |
| | F,Emissions dans l'air intérieur | A+/A+ |
| | Environmental Choice NZ | Approved |
| Environment | Byggvarudeklaration | BVD 3 |

Guides

| | | |
|------------------------------|----|--------|
| Installation+adhensive guide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |

| Product description | Methods | Product data |
|----------------------------|----------------|---------------------|
| Cleaning, stain removal | GB | English |
| | D | Deutsch |
| | F | Francais |
| | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer

| | | |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | OHSAS | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |
| | | |