

Product description	Method	Product specifications
Construction characteristics		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% polyamide
Fibre	Brand owner's	
Coloration	-	Continuous dyed
Backing	eTL	WT - Woven textile
Dimensions	CEN/TS 14159	Approx. 400 cm
Total thickness	ISO 1765	Apr 6,5 mm.
Surface pile thickness	ISO 1766	Apr 4,0 mm.
Tufts	ISO 1763	Apr 91.000 pr.m2
Total carpet weight	ISO 8543	Apr 2.350 g/m2
Pile yarn weight	eTL	590 g/m2
Surface pile density	ISO 8543.	Apr 0,120 g/cm3
Soil protection	eTL	Yes
Performance characteristics		
Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	ISO 717-2	24 dB
Acoustical absorption	ISO 354	0,20 aW
Suitability underfloorheating	eTL	Apr 0,11 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	5
Colour fastness to rubbing wet	ISO 105-X12	>3
Colour fastness to rubbing dry	ISO 105-X12	>3-4
Colourfast. to water patterned	ISO 105-E01	>4
Safety & Environment		
Fire classification	MK GODKENDELSE DIBT AbZ.no. VKF/AEAI EN 13501-1 Euroclass	Approved Z-156.601-440 Approved Cfl-s1
CE Labeling	EN 14041 CPR Declaration of Performance Notified body no. Ce Year Content of PCP EN 12673 Formaldehyde emission Slip resistance EN 13893	Certified 1021-CPR-006-2/16 DOP 1C-PA-WT 1021 07 DL NA Class DS
Indoor climate	DIM certificate BASTA Green Label Plus Emissions dans l'air intérieur GECA	No. 006 Registered Approved A+/A+
Environment	BRE Byggvarudeklaration BREEAM-NOR	Approved ENP 434 eBVD With WTA Backing

Product description	Method	Product specifications
	Environmental Product Decl. Cradle To Cradle Certified	EPD-EGE-20140054-CBC1-EN Silver certified
Guides		
Installation + adhesive guide	DK N S GB D F	Dansk Norsk Svensk English Deutsch Francais
Cleaning, stain removal	DK N S GB D F	Dansk Norsk Svensk English Deutsch Francais
Manufacturer characteristics		
Factory certification	ISO 9001 ISO 14001 EMAS DS/OHSAS DS 49001 CRuk TransQ	Audited and verified by BVC Audited and verified by BVC Audited and verified by BVC Audited and verified by BVC Audited and verified by BVC Member of Carpet Recycling UK Qualified