

# Contra Ecotrust

## Produktbeschreibung



Produktbeskrivelse	Metoder	Produktdata
<b>Konstruktion</b>		
Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	1/10
Luvmateriale	DIR 96/73, 96/74	100% Polyamid
Farvemethode	-	Continue
Bagside	eTL	Ecotrust 350, 100% recycled
Dimensioner	ISO 3018	48x48/96x96cm/Figura
Dimensionstabilitet fliser	EN 986	<0,2%
Totalhøjde	ISO 1765	Ca. 7,0 mm.
	.	0.28"
Slidlag	ISO 1766	Ca. 2,5 mm.
Noppeantal	ISO 1763	Ca. 160.000 pr.m2
Totalvægt	ISO 8543	Ca. 2.600 g/m2
	.	76.7 oz./yd2
Luvindsatsvægt	eTL	675 g/m2
	.	19.9 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,140 g/cm3
ege soil protection	eTL	Ja

### Egnethedsprøvnninger

Brugsområder	EN 1307	33 Erhverv - Kraftig brug
	Gulvbranchen	Klasse 33
Rullehjulseget	EN 985	Ja, konstant brug
Trappeget	EN 1963	Ja
Antistatiske egenskaber	eTL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	eTL	25 dB
Akustisk absorption	eTL	0,25 aW
Gulvvarmeegnet	ISO 8302	Ja
Lysrefleksion	eTL	Testrapport
Lysægthed	ISO 105-B02	>5
	AATCC 16	4.0
Gnideægthed våd	EN ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	EN ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed mønstrede/melerede	EN ISO 105-E01	>4
Cleaning	AATCC 138	4.0
Colour fastness to Ozone	AATCC 129	3.5
Colour fast.Oxides of Nitrogen	AATCC 164	4.0
Øvrige brugstests	ASTM D5252 Hexapod	4.0/3.5
	AATCC 134 Electrostat.propensity	1.7 kV

### Sikkerhed & Miljø

Brandklassifikation	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-441

Produktbeskrivelse	Metoder	Produktdata
CE Mærkning	CH,VKF/AEAI	Godkendt
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euro Class	Cfl-s1
	HRN, DIN4102-14	B1
	EN 14041	Certificeret
	CPR	1021-CPR-010-2/16
	Ydeevnedeklaration	DOP 5C-PA-ECT350
	Notified body no.	1021
Indeklima	Ce Year	12
	Skridsikkerhed EN 13893	Class DS
	DIM Certifikat	No.006
	M1	Med ECTA bagside
	BASTA	Registreret
	Green Label Plus	Godkendt
	Emissions dans l'air intérieur	A+/A+
	Environmental Choice NZ	Godkendt
	GECA	Godkendt
	Miljø	Byggvarudeklaration
Environmental Product Decl.		EPD-EGE-20150220-CBC1-EN
Cradle To Cradle		Bronze Certified
Recycled Content, ISO 14021		Ca. 18,0 %
Recycled Content for LEED		Ca. 18,0 %
LEED		Qualified

### Vejledninger

Montering, inkl. limguide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Producent

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified