## Rawline modular on Ecotrust 350, 100% Recycled

**Product Description** 





ECO
TRUST

Antismudsbehandlet
Antisailing protected
Schmutzabweisend
Traitée antisalissure



















29/06/2017 Page: 1

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Millitron dyed
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96cm/Figura
Dimensional stability	EN 986	<0,2%
Total thickness	ISO 1765	Apr 5,0 mm.
Total carpet weight	ISO 8543	Apr 2.350 g/m2
Pile yarn weight	eTL	345 g/m2
Soil protection	eTL	Yes
Performance characteristics		
Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noice	eTL	16 dB
Acoustical absorption	eTL	0,20 aW
Suitability underfloorheating	eTL	Apr 0,09 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
Ü	AATCC 16	4.5
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fastness to ozone	AATCC 129	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Other performance tests	ASTM D5252 Hexapod	5.0
Carlot performance tools	AATCC 134 Electrost.propensity	1,1 kV
Safety & Environment		
Fire classification	ASTM E-648	Class 1
CE Labeling	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	RUSSIA	Approved
	ASTM E 662	Approved
	EN 14041	Certified
	CPR	1021-CPR-010-1/16
	Declaration of Performance DBI	DOP 9711-5B
		1021
	Notified body no.	
	Ce Year	17
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA Class DC
	Slip resistance EN 13893	Class DS
Indoor climate	DIM certificate	No. 006



29/06/2017 Page: 2

Product description	Methods	Product data
Guides		
Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Installation tiles	Direction of installation	Quarter turn
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Manufacturer characteristics		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified

