

Epoca Texture 2000

Product Description

Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antialissure

contract
CERTIFICATE

ege
Kontaktpersonen

CE

A+

Recycling symbol

* Antismudsbehandlet er en beskyttelse mod smuds og vand. Det betyder, at du nemt kan fjerne smuds og vand med en fugtig klud. Det betyder også, at du kan holde dit gulv rent og glansende længere tid. Antisoiling protected is a protection against dirt and water. It means that you can easily remove dirt and water with a damp cloth. It also means that you can keep your floor clean and shiny for a longer time. Schmutzabweisend ist eine Schutzschicht gegen Schmutz und Wasser. Das bedeutet, dass Sie Schmutz und Wasser leicht mit einem feuchten Tuch entfernen können. Das bedeutet auch, dass Sie Ihren Boden länger sauber und glänzend halten können. Traitée antialissure est une protection contre la saleté et l'eau. Cela signifie que vous pouvez facilement éliminer la saleté et l'eau avec un chiffon humide. Cela signifie également que vous pouvez garder votre sol propre et brillant plus longtemps.



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	Approx. 400 cm
Total thickness	ISO 1765	Apr 15,5 mm. 0.61"
Surface pile thickness	ISO 1766	Apr 13,0 mm.
Tufts	ISO 1763	Apr 196.000 pr.m2
Total carpet weight	ISO 8543	Apr 3.550 g/m2 104.73 oz./yd2
Pile yarn weight	eTL	2.000 g/m2 59 oz./yd2
Surface pile density	ISO 8543.	Apr 0,140 g/cm3
Soil protection	eTL	Yes

Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	ISO 717-2	36 dB
Acoustical absorption	ISO 354	0,25 aW
Suitability underfloorheating	eTL	Apr 0,27 m2K/W
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colour fastness to water plain	ISO 105-E01	>3-4
Cleaning	AATCC 138	5.0
Colour fastness to ozone	AATCC 129	2.0
Colour fast.Oxides of nitrogen	AATCC 164	3.5
Other performance tests	ASTM D5252 Hexapod	4.0/ 3.5
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	2,9 kV

Safety & Environment

Fire classification	MK GODKENDELSE	Approved
	DIBT AbZ.no.	Z-156.601-441
	VKF/AEAI	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass

Product description	Methods	Product data
CE Labeling	EN 13501-1 Euroclass	Cfl-s1
	ASISO 9239.1-2003	3,30 KW/m2
	EN 14041	Certified
	CPR	1021-CPR-006-2/16
	Declaration of Performance	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	12
Indoor climate	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
	DIM certificate	No. 006
	Green Label Plus	Approved
Environment	Emissions dans l'air intérieur	A+/A+
	Environmental Product Decl.	EPD-EGE-20150283-CCA1-EN
	Cradle To Cradle Certified	Silver certified
	LEED	Qualified

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified



THE URGE TO EXPLORE SPACE