

Una Casa

Product description



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% Solution dyed Polyamide
Coloration	-	Solution dyed
Backing	eTL	WT - Woven textile
Dimensions	ISO 3018	400 cm
Total thickness	ISO 1765	Ca. 3,5 mm.
Total carpet weight	ISO 8543	Ca. 2.100 g/m ²
Pile yarn weight	eTL	400 g/m ²
ege soil protection	eTL	Yes

Performance ratings

Performance areas	EN15114 eTL	33 Commercial - Heavy Contract certifikat
Performance areas	Gulvbranchen	Klasse 33
Suitable for castor chairs	EN 985	Yes, constant use
Suitable for stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	17 dB
Acoustical absorption	eTL	0,15 aW
	Sound absorption class	E
Suitable for heated floors	ISO 8302	Yes
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to rubbing dry	EN ISO 105-X12	>3-4
Colour fastness to water plain	EN ISO 105-E01	>3-4

Safety & Environment

CE Labeling	Slip resistance EN 13893 EN 14041	Class DS Certified
EC Certificate	EN 14041	0845-CPD-CX10016C
Reaction to fire	DK,MK GODKENDELSE D,DIBT AbZ.no. CH,VKF/AEAI EN13501-1 euro class	Godkendt Z-156.601-675 Cfl-s1 Cfl-s1
CE Labeling	Declaration of Performance	9711-16C
Indoor air	DIM Certifikat LEED BASTA F,Emissions dans l'air intérieur	No.006 Green label plus Registered A+/A+
Environment	Byggvarudeklaration	BVD 3

Guides

Installation+adhensive guide	DK N S GB D	Dansk Norsk Svensk English Deutsch
------------------------------	-------------------------	--

Product description	Methods	Product data
Cleaning, stain removal	F	Francais
	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK